



Product Fact Sheet

Markets

Homeowners
Landscape Contractors
Rental Dealers

Applications

Aerating

EZair® Aerator

Heavy-Duty-Handles

Shaped for comfort and control - choice of two positions

Operator's Choice

To raise the tines, either lift up on the handle or pull back on the lever. To engage, simply push the lever forward.

Low Center of Gravity

The design of the machine allows for greater stability than any competitive unit.

Power to Spare

5.5 HP (Honda or B&S Intek) means more power for greater productivity - up to 33,000 sq.ft. per hour. The EZair® outperforms larger units.

Turn on a Dime

Heavy duty puncture proof casters add greatly to maneuverability and stability.

Why Fight It?

Puncture proof outboard drive wheels and heavy-duty differential provide traction assistance during operation and make turning a breeze.



Changing the Shape of Aerators

- **Maneuverability** - "Z" in **EZair®** stands for zero turn
- **Rear casters** - the **EZair®** turns on a dime with assist from the front drive wheels
- **Easy to load and unload** - Two sets of lift handles front and rear or just drive it up onto a trailer
- **Independent throttle control** - Productivity up to 33,000 sq. ft. per hour
- **Weight lifts on and off easily** - No water drums to fill or weights to slide in from the side
- **Low center of gravity** - Tines penetrate evenly on slopes
- **Low service cost** - Replaceable spiders and tines
- **Ease of maintenance** - Six greasable pillow block bearings and heavy O-ring chain



Weight Bar

(Part # 360162)
One 36 pound weight lifts on and off easily from the top. No need to add water or slide weights in from the side or bottom.



Tine Assembly

(Part # 360100)
Patent-pending design allows operator to easily replace single spider as required. Save time and money.

For pricing and availability, contact your authorized Billy Goat Dealer.

Product Fact Sheet



Rear Casters

Aid significantly in turning the **EZair**[®] to follow the contour of landscaping and buildings. At the end of a straight run, the casters and front differential allow the unit to turn on a dime.



Independent Throttle

Unlike other units, the throttle controls ground speed and productivity. Slow down for tight quarters or rev it up for longer runs.




Lift Handles

Two handles on each side are optimally placed for lifting (two people required).



Safety First

Guard protects operator's feet from tines and eliminates flex in the rear caster assembly.



Easy Service

The cover comes off easily allowing for immediate access to maintenance points.

Specifications

Power	Model AE551 - 5.5 HP B&S OHV Model AE551H - 5.5 HP Honda OHV
Performance	Aerating Width - 19" Aerating Depth - 2.75" Aerating Pattern - 3.75" x 7" Up to 9 plugs per square foot
Assembly	Coring Tines 30 (0.75") hardened
Wheels	Front - 10.5" x 3" (puncture proof) Rear - 8" x 2" (puncture proof)
Width	30.5"
Length	57"
Height	54"
Weight	289 lbs. (Removable weight bar = 36 lbs.)
Productivity Range	Up to 33,000 sq. ft. per hour at 3400 RPM

Find your local Billy Goat Dealer under "Find a Dealer" at www.billygoat.com